

Technical Specification

September 2023

	Contacts
Page 2	Logistics
	Stage Measurements
	Scenery
	Special Effects & Health and Safety
	Flying Systems
Dago 2	House Tabs
Page 3	Dressing Rooms
	Communications
Page 4	Lighting Equipment
Page 5	Sound Equipment
	Digital Cinema and Alternative Content
	Power
Page 6	Rostra
	Masking
	Stage Management
Page 7	Additional Equipment
Page 7	Staffing

Contacts		
Technical Manager	Jack Chambers Jack.chambers@inspireall.com 01707 645005 [Ex.1001]	
Senior Projectionist & Technician	El	
	Gary Fisher	
Apprentice Technician	Zara Gates Max Green	

Logistics

Entrance to auditorium from street level, Entrance to stage from Stairs SL or ramp onto stage during show Get-in/out

Stage Door Dimensions:

Height: 2.55m (8'5")
Width: 1.18m (3'10")

Minimal parking is available in the loading area outside of the stage door. This area must be clear during performances to allow for emergency exits and emergency vehicles. Additional parking is available adjacent to the theatre and in the underground car park beneath the theatre.

Stage Measurements		
Upstage Width:	14.70m (48′2″)	
Downstage Width Min: Proscenium arch in	8.83m (28'11")	
Downstage Width Max: Proscenium arch out	13.13m (43′1″)	
Depth:	6.38m (20′95″)	
Stage Thrust: When installed	1.22m (4'0")	
Proscenium Arch Height:	4.23m (14′17″)	

Scenery

All scenery should conform to theatre licensing regulations.

See conditions of hire: Schedule D: 8,9

The theatre's duty technician may fire test any scenery brought in to the theatre. Please speak to technical staff if you have any queries.

Special Effects & Health and Safety

For the use of pyrotechnics, smoke, dry ice, fire arms, strobe or any other special effects, Wyllyotts requires a minimum of **14 days'** notice provided to us in writing for your request to be granted.

Wyllyotts Theatre requires you to submit all paperwork (including: risk assessment and safe system of work) with notice as stated above. Should you require assistance with this please contact the Technical Manager.

Wyllyotts Theatre reserves the right to refuse the use of any special effects, rigging, electrical equipment and access equipment should you be unable to provide adequate risk assessment, safe system of work and certificates.)

Flying Systems

11 Hemp Lines operated from Stage Right

SWL of 90kg Hemp 10 SWL of 125kg

4 Pilewind motors for lighting bars

SWL of 500kg

3 Overhead, 1 Front of House

For more information see flying plot.

1 Fixed lighting bar front of house (advanced 2) SWL of 100kg

> 2 Fixed scenery bars over stage SWL of 100kg

6 Fixed horizontal bars running length of wings Split 3 x SL & 3 x SR

SWL of 100kg

10 Fixed vertical bars evenly distributed along auditorium walls Split 5 x SL & 5 x SR

House Tabs

Wyllyotts' red crushed velvet tabs are motorised and have a variable running speed with a maximum of 9 seconds. They can be operated from the prompt desk, sound control area or the lighting box. Variable speed control is only adjustable from prompt desk.

Dressing Rooms		
Dressing Room 1	Up to 12 people 3 hand basins and 7 lit mirrors	
Dressing Room 2	Up to 7 people 1 hand basin, shower and 4 lit mirrors	
Dressing Room 3	Up to 7 people 1 hand basin, shower and 4 lit mirrors	
Gallery	Up to 25 people	

Additional dressing room spaces are available by prior arrangement with the Theatre Management All dressing rooms have 6' costume rails and 2 safes Keys are obtainable from the Duty Technician. Loss of keys will be charged to the client.

Communications

Tecpro Intercom System installed with the following positions:

Prompt Desk

Stage Right

Lighting/Projection control room

Sound Control

House Left & Right Followspot Positions

5 x SMH210 Headset

2 x DT109 Headset

5 x DT108 Headset

7 x BP111 Beltpack

3 x ASL Beltpack

	L	.ighti	ng Equipment			
Power	Three Phase 200Amp Supply					
Dimming	Strand WallRack Digital Dimmers providing 96 x 10 _A Circuits LSC E-Pro Digital Dimmers in portable rack providing 24 x 10 _A Circuits via 4 Socapex Out Wyllyotts can provide 4 x 20m Socapex cable and 4 x fan out					
Control			ETC Ion Xe 20			
	1-6		FOH Perch SL			
	7-14		Advanced 2 (paired outer to inner)			
	15-20		FOH Perch SR			
Dimmer	21-38		Advanced 1 (37 & 38 paired atouter)			
Distro	39-40		Front of stage dip circuits			
Distro	41-56		LX1 (+ 2 x 16 _A Hard Power)			
	57-72		LX2 (+ 2 x 16 _A Hard Power)			
	73-88		LX3 (+ 2 x 16 _A Hard Power)			
	89-96		Stage dip circuits paired SL & SR			
		7	Strand SL 15/32° Profile Spots 575w			
	D 61	6	Strand SL 23/50° Profile Spots 575w			
	Profiles	6	Selecon 24/40° Profile Spots 1200w			
		9	Selecon 18/34° Profile Spots 1200w			
			Source 4 Jnr 50° Profile Spots 575w			
		5	Selecon Rama PC 1200w			
	Fresnels &	4	Selecon Rama Fresnel 1200w			
	PCs	5	Starlette Fresnel 1000w			
	1 C3	8	Strand Patt. 743 Fresnels 1000w			
		17	Par 64 1K (Assorted lamps available)			
Luminaires	Par Can	12	Koupo (S4 Par Copies) 575w			
		4	Par 64 Floorcans			
	Floods	15	Coda 1 500w			
		11	Chauvet Rogue R2 LED Moving Wash			
		5	ETC Coloursource Cyc Wash			
	Intelligent	4	Pulse LED Batten*			
		14	Chauvet Par56-FC			
		2	Chauvet Reve – E3 Spot 50°			
		2	LEDJ Event Spot RGBW			
	Followspot 2		Robert Juliatt Manon (1200w MS) on RJ leg stands			
Additional lighting equipment can be hired by arrangement with the Technical Manager.						
		recili	iicai manayer.			

	Sound Ed	quipme	ent		
5	Stage Boxes SL/SR:		8 XLR Send 4 XLR Return		
Distro	Full patchii	Full patching facility as control position			
	Dante	32/16	Digital Snake DSL		
Mixer	Positioned aud	Yam litorium lei	aha QL5 ft to the rear of raked seating		
	FOH Mid/Hi	L&R	2 x JBL SRX 722		
	,	С	1 x JBL SRX 712		
	Sub	С	1 x JBL SRX 728s (Dual 18")		
Output		Mid	4 x JBL Control 28 (20' from Prosc.)		
·	Delay	Rear	4 x JBL Control 28 (40' from Prosc.)		
	Monitoring	4 x JBL G2 Eon (Active) 5 x Ohm TRS-112 (Passive)			
Amplifiers	FOH	4 x QSC PLX2502 1 x QSC CX4			
7	Foldback				
Processing	Built in to Yamaha QL5				
	3 x Shure SM58				
	3 x Shure SM57				
	2 x AKG D 321				
	1 x AKG C 568 EB				
Microphones	2 x Shure SMbeta87				
	1 x Sennheiser MD 421				
	2 x AKG SE300 with CK91 head				
	3 x Sure SMbeta98 (drummics)				
	1 x AKG D112 (kick drum mic)				
	1 x EMO Single DI				
DI	2 x Stageline Stereo DI				
	1 x BSS Single DI				
Playback	1x Mac Mini - Running Qlab				

Digital Cinema and Alternative Content		
	Dolby Show Server, DCP	
Formata	HDMI/Vga – From Anywhere within the theatre	
Formats	Live Satellite Streaming	
	Blu-ray LG player	
Screen	Perlux 180, electrically flown roller screen. See flying plot	
Screen	for location. Takes 3 mins to roll in.	
Projection	Barco CP2K-15c	
	Christie LX700 (7000ansi Lumen)	
Sound	Dolby CP650 Processor	
	With:	
	7.1 Surround from Dolby Show Server	
	5.1 Surround from Tascam DVD Player	
	Stereo from all other sound sorces	

Please contact the Technical Department as early in advance as possible if you plan on using our cinema equipment.

you plan on using our cinema equipment.				
Power				
Single phase, 100amp, Busbar Chamber situated upstage left fitted				
		RCD (sound phase)		
1	3 phase, 125amp CEEFORM	socket upstage left		
8	13amp sockets	fitted 30mA RCD, prompt corner (LX phase)		
4	13amp sockets	fitted 30mA RCD, upstage left wall (sound phase)		
4	13amp sockets	fitted 30mA RCD, upstage right wall (sound phase)		
1	16amp sockets	stage right (LX phase)		
2	13amp sockets	stage right (LX phase)		
2	13amp sockets	fitted RCD stage front at floorlevel		
2	16amp sockets	per stage LX bar		
Rostra				
6	8' x 4'	Steeldeck		
2	4' x 4'6"	Steeldeck		
2	3′	Steeldeck Treads		
6	1mx2m Alideck			
24"	Legs for the Steeldeck			
48"	Legs for the Steeldeck			
12"	Legs for the Steeldeck			
30cm	30cm Legs for Alideck			
	Stage thrust extension comprises	of all Steeldeck sections on 48" legs		
Masking				
3	Black serge tabs (2 constantly flown upstage & mid-stage)			
3		ll borders 5′ (1 Pleated)		
4	6' x 18' twill soft legs			
2	2 Black twill borders 3' (Stored)			
Stage Management				
25		Stage Weights		
12	Stage Braces of assorted lengths			
16	Boom Arms			

4	Boom Bases

Additional Equipment			
	2	Sennheiser Ew G4 handheld radio mic set (channel 70)	
Sound	12	Sennheiser Ew-D SK bodypack radio mic sets (channel 41)	
	3	Sennheiser MKH 416	
	14	Sennheiser MKE Essential on headsets	
	2	18" Mirror ball	
Lighting	2	Telrad followspot sights	
	1	RGB LED Star cloth 36' x 18'	
Stage	1	ASL BlinQ	
Management	1	Q Light System with 4 outstations	
	1	Haze Base Pro (2ch DMX or stand alone)	
	2	Chauvet DJ Geyser P6 Fog Machine	
Effects	2	UV Cannons	

For a quotation on these additional hire items, please contact the Technical Manager.

Staffing

Wyllyotts Theatre provides two members of technical staff on site at all times whilst you are occupying the Theatre. They are both there to assist you on the best way to achieve the result you require. They can train any of your technical staff, stage crew or stage management in the correct safety procedures of the theatre.

Wyllyotts Theatre can provide additional crew for you, if you require, but this will be at an additional cost. We endeavour to keep these additional costs as low as possible.

Thank you,

Jack Chambers Technical Manager